





SENKO d.o.o. Vladimira Nazora 22, Štefanec HR - Čakovec 40 000 T +385 (0)40 337 344 / E info@senko.hr www.senko.hr

DECLARATION OF PERFORMANCE

Nr. E300035412-DOP22-5-80-EN According to Regulation (EU) 305/2011

1. Unique identification code of the product type :

type . C-25, \$

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11, Paragraph 4:

3. Intended use or uses of the construction product, in accordance with the appliance harmonized technical specification, as foreseen by the manufacturer:

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11, Paragraph 5:

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2:

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

C-25, Solid fuel cooker for central heating with oven

E 2280, E 2580

Space heating, hot-water heating, cooking and baking

SENKO d.o.o., Vladimira Nazora 22, Štefanec HR - 40 000, Čakovec – Republic of Croatia

System 3

The notified laboratory Engineering Test Institute, Public Enterprise, Brno, Nr.1015 performed the determination of the product type on the basis of type testing under System 3 and issued test report Nr. 30-11665/1

8. Declared performance

Harmonized technical specification	EN 12815:2001/A1:2004/AC:2007
ESSENTIAL CHARACTERISTICS	PERFORMANCE
Fire safety	I LIN ONWANGE
Reaction to fire	A1
Minimum distance to flammable materials	rear = 200 mm sides = 200 mm above = 1000 mm front = 800 mm
Risk of burning fuel falling out	Pass
Emission of combustion products (13% O ₂) at nominal heat output	CO [0,3 %]
Surface temperature	Pass
Electrical safety	NPD*
Cleanability	₽ass
Maximum operating pressure	3 bar
Flue gas temperature at nominal heat output	T [290 °C]
Mechanical resistance (to carry a chimney/flue)	NPD*
Thermal output	
Nominal heat output	25 kW
Space heat output	7 kW
Water heat output	18 kW
Energy efficiency	η [75 %]
*No Performance Determined	1 11 10 70]

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Saša Senčar (technical Manager)

Štefanec, 01/07/2013

