

## Declaration of performance under Regulation (EU) 305 / 2011

No 011 : CPR 58 / 27.06.2011

1. The Unique identification code of the product type:

Solidfuel appliance with hot water supply EN 12815:2001 / A1: 2004/AC: 2007

2. Type series of serial number or other element allowing identification of the construction products :

Stoves for solid fuel type designation SUPER THERMO MAGNUM , designed for intermittent operation – classification of the stove : 1 , according to Table EN 12815 / A1 .

Basic technical data of stoves

Type	Dimension ( mm )			Rated power ( kW ) Wood/Coal	Fuel consumption ( kg / h )		Flue	Operating move ( Pa )
	height	length	depth		wood	coal		
Super Thermo Magnum	865	1070	660	20,0 / 20,0	5,10	7,10	130 mm	12

Further information can be found in the catalogue of producer Milan Blagojevic A.D , Smederevo , Serbia.

3. The intended use of construction products in accordance with the relevant harmonized technical specification

Stoves for solid fuel type designation SUPER THERMO MAGNUM, are designed for central heating and central heating

4.Name , company , or registered trademark and contact address of manufacturer :

Company : Milan Blagojević a.d.

Registered office : Đure Strugara 20  
11300 Smederevo, Serbia

ID : 7342756

00 381 26 633 709 development department

00 381 26 621 443 sales department

00 381 26 229 941 fax.

5. The system of assessment and verification of constancy of performance of products :

3 ( annex V, point 1,4 Regulation of the European Parliament and the Council ( EU ) no. 305 / 2011 of the day 9.3.2011)

6.Products are covered by a harmonized standard :

EN 12815 : 2001 / A 1 : 2004 / AC : 2007 assessment and initial type testing made by TERMOLAB

Ltd. Novi Iskar, 18 Kesten str. , Bulgaria., authorization number CPD 11 - NB 2033 , has issued a test report number 38 / 17.09.2010 for initial type testing.

7. Declared performance specified in the declaration apply to all products listed in paragraph 2

Harmonized technical specification	EN 12815 : 2001 / A 1 : 2004 / AC : 2007
Main features	features
Fire safety	
Distance from flammable materials	Minimal distance in mm Real wall = 500 Side walls = 500 Front wall = 800
Risk of burning fuel falling	Pass
The emission	CO wood = 0,072%      coal = 0,066%
The surface temperature	Pass
Electrical safety	NPD
Clean ability	Pass
Max. operation pressure	2 bar
Flue gas temperature at rated thermal output	T wood = 178,7°C      coal = 128,9°C
Mechanical resistance ( load flue connection )	NPD
Heat output	
Nominal output Wood / Coal	20,0 kW / 20,0 kw
Space heating performance Wood / Coal	10,0 kW / 7,0 kW
Heat capacity of water Wood / Coal	10,04 kW / 13,0 kW
Energy efficiency	Wood 87%      Coal 89%

8. Performance of the product of paragraph 1 and 2 are consistent with the characteristics listed in Section 7.

The declaration of performance is issued under the sole responsibility of the manufacturer to in paragraph 4.

Signed for and on behalf of the manufacturer:

Mr. Mileta Djurićanin , director of development  
(name and position)



Mrs. Mira Trikić  
( executive director)




Smederevo , 11.07.2013  
( place and date )

„NPD“ (No Performance Determined),

